

The Refrigerated Bath comes with an air-cooled refrigerating unit, housing and a stainless steel tank. The refrigerating unit can work continuously.

*Together with the immersion thermostats, the bath can be used up to 200°C.

Technical data according to DIN 12876

Operating temperature range	-20...200 °C
Cooling power	
at 20°C	0,25 kW
at 0°C	0,2 kW
at -10°C	0,12 kW
at -20°C	0,05 kW
Refrigeration machine	air-cooled, natural refrigerant
Refrigerant	R290
Refrigerant quantity	0,041 kg
Bath volume	12 ltr
Width bath opening WxD/ bath depth	290x320/ 150 mm
Overall dimensions WxDxH **	350x560x263 mm
Net weight	20 kg
Power supply requirement	115V 1~ 60Hz
max. current	2,6 A
Fuse (1 phase)	4 A
min. ambient temperature	5 °C
max. ambient temperature	40 °C



Order-No.: 2009.0003.99

from Serial-No.:

110077

1.2/11

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions.

Accessories and periphery: Drain valve with cap #6839, adjustable base #19654, test tube racks Type 1-4,

Bath covers in various versions: see catalogue.

* standard equipment

Output data valid for: Room temperature 20°C

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and +2% frequency -> not allowed!

-5%voltage and -2% frequency -> allowed.

** Please respect space requirements.